

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: ROPETEX THIN LUBE 30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Anticorrosion product Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier	SCM CITRA OY Asessorinkatu 3-7 20780 Kaarina Finland
Telephone:	+358 2 5115511
Contact Person:	SCM Citra Product Director
E-mail:	edc.sales@scmcitra.com
.4 Emergency telephone number:	+45 82 12 12 12

SECTION 2: Hazards identification

1

-

. . . .

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards		
Flammable liquids	Category 3	H226: Flammable liquid and vapor.
Health Hazards		
Specific Target Organ Toxicity - Single Exposure	Category 3	H336: May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure	Category 1	H372: Causes damage to organs through pro- longed or repeated exposure.
Aspiration Hazard	Category 1	H304: May be fatal if swallowed and enters air- ways.
Environmental Hazards		
Chronic hazards to the aquatic environment	Category 2	H411: Toxic to aquatic life with long lasting ef- fects.



Hazard summary Physical Hazards:	Can form flammable vapour-air mixtures during the application.
Health Hazards Inhalation:	Has a narcotic effect.
Skin Contact:	At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Ingestion:	If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.
2.2 Label Elements Contains:	White Spirit, low viscous
Signal Words:	Danger
Hazard Statement(s):	H226: Flammable liquid and vapor. H336: May cause drowsiness or dizziness. H372: Causes damage to organs through prolonged or repeated expo- sure. H304: May be fatal if swallowed and enters airways. H411: Toxic to aquatic life with long lasting effects.
Precautionary Statemen	ts
Prevention:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260: Do not breathe dust/fume/gas/mist/vapors/spray. P273: Avoid release to the environment.
Response:	P301+P310: IF SWALLOWED: Immediately call a POISON CEN- TER/doctor. P331: Do NOT induce vomiting.
Disposal:	P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Supplemental label info	rmation EUH066: Repeated exposure may cause skin dryness or cracking.
2.3 Other hazards:	By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients



3.2 Mixtures

General information:

Mixture based on severely refined mineral base oils and corrosion preventive agents in volatile hydrocarbons with a flashpoint below 55°C.

Chemical name	ldentifier		REACH Registra- tion No.	Notes
White Spirit, low viscous	EC: 919-446-0	50,00% - <100,00%	01-2119458049-33	
diacetone alcohol	EINECS: 204-626-7	0,10% - <1,00%	01-2119473975-21	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification	
White Spirit, low viscous	EC: 919-446-0		Asp. Tox. 1;H304, Flam. Liq. 3;H226, STOT SE 3;H336, Aquatic Chronic 2;H411, STOT RE 1;H372
diacetone alcohol	EINECS: 204-626-7	CLP:	STOT SE 3;H335, Eye Irrit. 2;H319, Repr. 2;H361d

CLP: Regulation No. 1272/2008.

specific concentration limit

Chemical name		specific concentra- tion limit		Category	Hazard state- ments
diacetone alcohol	EINECS: 204-626-7	>= 10 %	Serious eye irritation	2	H319

For the wording of the listed hazard statements refer to section 16.

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

ECTION 4: First aid measures

Instantly remove any clothing soiled by the product.				
4.1 Description of first aid measures				
Supply fresh air; consult doctor in case of symptoms.				
Promptly wash eyes with plenty of water while lifting the eye lids.				
Get medical attention if symptoms occur. Take off immediately all contami- nated clothing. Rinse skin with water [or shower]. Wash with water and soap; pay attention: skin degreasing product.				
Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.				



4.2 Most important symptoms and effects, both acute and delayed:	If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Headache.	
4.3 Indication of any immediate medical attention and spe-	Get medical attention if symptoms occur.	

SECTION 5: Firefighting measures

cial treatment needed

	General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be inef- fective in fighting the fire. Fight fire from a protected location. Move con- tainers from fire area if you can do so without risk.
5.1	Extinguishing media Suitable extinguishing me- dia:	CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant add-ed
	Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
5.2	Special hazards arising from the substance or mix-ture:	Can form explosive vapor-air mixtures at higher temperatures.
5.3	Advice for firefighters Special fire fighting proce- dures:	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
	Special protective equip- ment for fire-fighters:	Firefighters must use standard protective equipment including flame retard- ant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Self-contained breathing apparatus and full protective cloth- ing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro- tective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. In case of spills, beware of slippery floors and surfaces. Keep away from sources of ignition - No smoking.
6.2 Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Prevent from spreading (e.g. by binding or oil barriers). Environmental manager must be informed of all major spillages. Do not allow to enter drainage system, surface or ground water.
6.3 Methods and material for containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.



6.4 Reference to other sec- tions:	See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.
	Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe han- dling:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Use only in well- ventilated areas. Risk of vapor concentration on the floor and in low-lying areas. Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.
7.2 Conditions for safe storage, including any incompatibili- ties:	Store locked up. Store in a well-ventilated place. Store in a cool place. Lo- cal regulations concerning handling and storage of waterpolluting products have to be followed. The precautions for storing and handling of flammable liquids have to be kept. Local regulations for common storage of flammable liquids have to be followed. Do not heat up to temperatures close to the flash point.
7.3 Specific end use(s):	Not applicable

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Exposure Lim	it Values	Source
Base oil, low viscous - Mist.	GV		1 mg/m3	Denmark. Work Environment Authority. Expo- sure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)
Hydrocarbons, low viscous	GV	25 ppm	180 mg/m3	Denmark. Work Environment Authority. Expo- sure Limits for Substances & Materials, An. 2 & 3, as amended
diacetone alcohol	GV	50 ppm		Denmark. Danish List of Organic Solvents, Danish Labor Inspectorate (08 2007)
diacetone alcohol	GV	50 ppm	240 mg/m3	Denmark. Work Environment Authority. Expo- sure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment



General information:	Wash hands before breaks and after work. Use personal protective equip- ment as required. Personal protection equipment should be chosen accord- ing to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be ad- hered to inhandling the chemicals or the mineral oil products.
Eye/face protection:	Safety glasses (EN 166) recommended during refilling. Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.
Skin protection Hand Protection:	Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: >= 480 min Recommended thickness of the material: >= 0,38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recom-
	mended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety direc- tions. The exact break through time has to be found out by the manufactur- er of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pock- ets. Wear suitable protective clothing.
Respiratory Protection:	Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.
Thermal hazards:	Not known.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated foot- wear that cannot be cleaned.
Environmental Controls:	No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state:	liquid
Form:	liquid
Color:	Brown
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	substance/mixture is non-soluble (in water) Not applicable
Freezing point:	Not applicable for mixtures
Boiling Point:	Value not relevant for classification
Flash Point:	40 °C
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification



Flammability Limit - Upper (%)–:	Value not relevant for classification
Flammability Limit - Lower (%)–:	Value not relevant for classification
Vapor pressure:	Not applicable for mixtures
Vapor density (air=1):	Not applicable for mixtures
Density:	0,82 g/cm3 (15 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Kinematic viscosity:	< 20,5 mm2/s (40 °C)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Material is stable under normal conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Heat, sparks, flames.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and oth- er toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral Product:	
Specified substance(s)	Not classified for acute toxicity based on available data.
White Spirit, low viscous	LD 50 (Rat): > 15.000 mg/kg
diacetone alcohol	LD 50 (Rat): 3.020 mg/kg (OECD 401)



Dermal Product:		
	Not classified for acute toxicity based on available data.	
Specified substance(s) diacetone alcohol	LD 50 (Rabbit): 13.750 mg/kg	
Inhalation Product:		
Specified substance(s)	Not classified for acute toxicity based on available data.	
White Spirit, low viscous	LC 50 (Rat, 4 h): > 13,1 mg/l	
Skin Corrosion/Irritation: Product: Specified substance(s)	Based on available data, the classification criteria are not met.	
diacetone alcohol	OECD 404 (Rabbit, 24 h): Not irritant.	
Serious Eye Damage/Eye Ir Product: Specified substance(s)	ritation: Based on available data, the classification criteria are not met.	
diacetone alcohol	OECD 405 (Rabbit): Irritating to eyes.	
Respiratory or Skin Sensitiz Product:	zation: Skin sensitizer: Based on available data, the classification criteria are not met. Respiratory sensitizer: Based on available data, the classification criteria are not met.	
Specified substance(s) diacetone alcohol	(Guinea Pig) No sensitizing effect (guinea pig); OECD 406	
Germ Cell Mutagenicity Product:	Based on available data, the classification criteria are not met.	
Carcinogenicity Product:	Based on available data, the classification criteria are not met.	
Reproductive toxicity Product:	Based on available data, the classification criteria are not met.	
Specific Target Organ Toxicity - Single Exposure Product: Based on available data, the classification criteria are met.		
Specific Target Organ Toxic Product:	city - Repeated Exposure Based on available data, the classification criteria are met.	
Aspiration Hazard Product:	May be fatal if swallowed and enters airways.	
Other adverse effects:	No data available.	



SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity Product:	Based on available data, the classification criteria are not met.
Fish Specified substance(s) White Spirit, low viscous	LC 50 (Fish, 96 h): 10 - 30 mg/l
diacetone alcohol	LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)
Aquatic Invertebrates Specified substance(s) White Spirit, low viscous	EC 50 (Water Flea, 48 h): 10 - 20 mg/l (OECD 202)
diacetone alcohol	EC 50 (Water Flea, 48 h): > 1.000 mg/l (OECD 202)
Chronic ToxicityProduct:	Based on available data, the classification criteria are met.
Aquatic Invertebrates Specified substance(s) diacetone alcohol	NOEC (Water Flea, 21 d): 100 mg/l (OECD 211)
Toxicity to Aquatic Plants Specified substance(s) White Spirit, low viscous	EC 50 (Alga, 72 h): 4,6 - 10 mg/l (OECD 201)
diacetone alcohol	EC 50 (Alga, 72 h): > 1.000 mg/l (OECD 201)
12.2 Persistence and Degradabili	ty
Biodegradation Product: Specified substance(s)	Not applicable for mixtures
diacetone alcohol	98,51 % (28 d, OECD 301A) Readily biodegradable
12.3 Bioaccumulative potential Product:	Not applicable for mixtures
12.4 Mobility in soil: Product:	Not applicable for mixtures

- **12.5 Results of PBT and vPvB** The product does not contain any substances fulfilling the PBT/vPvB criteria. **assessment:**
- **12.6 Other adverse effects:** Toxic to aquatic life with long lasting effects.



SECTION 13: Disposal conside	erations
13.1 Waste treatment method	S
General information:	Dispose in accordance with all applicable regulations.
Disposal methods:	Discharge, treatment, or disposal may be subject to national, state, or loca laws.
European Waste Codes	
	12 01 99: wastes not otherwise specified

SECTION 14: Transport information

ADR/RID 14.1 UN Number: 14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es) Class: Label(s): Hazard No. (ADR): Tunnel restriction code: 14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user:	UN 1993 FLAMMABLE LIQUID, N.O.S.(White Spirit, low viscous, diacetone alcohol) 3 3 30 (D/E) III Dangerous for the environment -
IMDG 14.1 UN Number: 14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es) Class: Label(s): EmS No.: 14.3 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user: IATA	UN 1993 FLAMMABLE LIQUID, N.O.S.(White Spirit, low viscous, diacetone alcohol) 3 3 F-E, S-E III P -
14.1 UN Number: 14.2 Proper Shipping Name: 14.3 Transport Hazard Class(es): Class: Label(s): 14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user:	UN 1993 Flammable liquid, n.o.s.(White Spirit, low viscous, diacetone alco- hol) 3 3 III Dangerous for the environment -

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.



Product name: ROPETE	X THIN LUBE 30
SECTION 15: Regulator	y information
15.1 Safety, health and	l environmental regulations/legislation specific for the substance or mixture:
EU Regulations	
Regulation (EC) No	o. 2037/2000 Substances that deplete the ozone layer: none
Regulation (EC) No	o. 850/2004 on persistent organic pollutants: none
National Regulation	ons
	e-numbered products ready to use mixture : 5-3
15.2 Chemical safety as sessment:	s- No Chemical Safety Assessment has been carried out.
SECTION 16: Other info	rmation
Revision Information:	Vertical lines in the margin indicate an amendment.
	ments in section 2 and 3
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Other information:	The classification complies with the current EU lists; however, it has been supplemented with expert literature information and information provided by/about our company. It was derived from the test data and/or the application of the conventional method.
Revision Date:	04.02.2021
Disclaimer:	The data contained in this safety data sheet are based on our current
Discidinier.	knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property
	nor the suitability of the product for any specific technical application be de- duced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of pro- cessing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no sig- nature.