

S2 endless polyester flat slings



This professional webbing sling is extremely suitable for intensive industrial use.

Properties

- Simplex design.
- WLL stripes, each stripe is 1 ton (up to 10 tons).
- 1t load capacity for each 30 mm webbing width.
- Available up to 10 Ton.

Standard delivery

- Packed in plastic including REMA manual.

Norm:

- EN1492-1

S2-PES					
	W.L.L (kg)	W.L.L (kg)	W.L.L (kg)	W.L.L (kg)	W.L.L (kg)
1.000 kg	1.000	800	2.000	1.400	1.000
2.000 kg	2.000	1.600	4.000	2.800	2.000
3.000 kg	3.000	2.400	6.000	4.200	3.000

Type	Usefull length (m)	Cicumference length (m)	1000 KG	2000 KG	3000 KG
Width			30 mm	60 mm	90 mm
			ProductId	ProductId	ProductId
S2-PE-0.5M	0.5	1	1212031	1212061	1212091
S2-PE-1M	1	2	1212035	1212065	1212095
S2-PE-1.5M	1.5	3	1212037	1212067	1212097
S2-PE-2M	2	4	1212039	1212069	1212099
S2-PE-2.5M	2.5	5	1212041	1212071	1212101
S2-PE-3M	3	6	1212043	1212073	1212103
S2-PE-3.5M	3.5	7	1212045	1212075	1212105
S2-PE-4M	4	8	1212047	1212077	1212107
S2-PE-4.5M	4.5	9	1212049	1212079	1212109
S2-PE-5M	5	10	1212051	1212081	1212111