

**S5 EX polyester roundslings**



Extra professional round sling extremely suitable for intensive industrial use. This type of round sling has proven itself for years in the German heavy industry.

**Properties**

- WLL stripes, each stripe is 1 ton (up to 10 ton).
- Continuous marked with the load capacity.
- High-quality herringbone polyester cover, a very strong and wear-resistant cover is obtained by weaving a strong monofil textile thread.
- Higher wear resistance due to the rib structure on the woven cover.
- Sleeve protected label.

**Standard delivery**

- Packed in plastic including REMA manual.

**Norm:**

- EN1492-2



Sleeve protected label

S5-EX					
	W.L.L (kg)	W.L.L (kg)	W.L.L (kg)	W.L.L (kg)	W.L.L (kg)
1.000 kg	1.000	800	2.000	1.400	1.000
2.000 kg	2.000	1.600	4.000	2.800	2.000
3.000 kg	3.000	2.400	6.000	4.200	3.000
4.000 kg	4.000	3.200	8.000	5.600	4.000
5.000 kg	5.000	4.000	10.000	7.000	5.000
6.000 kg	6.000	4.800	12.000	8.400	6.000
8.000 kg	8.000	6.400	16.000	11.200	8.000
10.000 kg	10.000	8.000	20.000	14.000	10.000

Type	Usefull length (m)	Cicumference length (m)	1000 KG	2000 KG	3000 KG	4000 KG	5000 KG	6000 KG	8000 KG	10.000 KG
			ProductId	ProductId	ProductId	ProductId	ProductId	ProductId	ProductId	ProductId
S5EX-PE-1M	1	2	1321001	1323001	1325001	1326001	1327001	1328001	1329001	1331001
S5EX-PE-1.5M	1.5	3	1321003	1323003	1325003	1326003	1327003	1328003	1329003	1331003
S5EX-PE-2M	2	4	1321005	1323005	1325005	1326005	1327005	1328005	1329005	1331005
S5EX-PE-2.5M	2.5	5	1321007	1323007	1325007	1326007	1327007	1328007	1329007	1331007
S5EX-PE-3M	3	6	1321009	1323009	1325009	1326009	1327009	1328009	1329009	1331009
S5EX-PE-3.5M	3.5	7	1321010	1323010	1325010	1326010	1327010	1328010	1329010	1331010
S5EX-PE-4M	4	8	1321011	1323011	1325011	1326011	1327011	1328011	1329011	1331011
S5EX-PE-5M	5	10	1321013	1323013	1325013	1326013	1327013	1328013	1329013	1331013