

RTRS Skates



The steering platform skate running on bearings makes manoeuvring with heavy loads easier.

Properties

- Polyurthane rollers running on bearings.
- Polyurthane rollers will not damage floors.
- Platforms have anti-slip rubber coatings.
- Can be easily placed or positioned by means of the hand grip.

Norm:

- EN12100

| Type | WLL (kg) | Number of rollers | Steering platform L x W x H (mm) | Dimension skate L x W x H (mm) | Turntable (mm) | Length of lever (kg) | Weight (kg) | ProductId |
|-----------|----------|-------------------|----------------------------------|--------------------------------|----------------|----------------------|-------------|-----------|
| RTRS-8.0T | 8.000 | 4 | 230 x 230 x 110 | 170 x 140 x 110 | Ø 150 | 800 | 31 | 4250108 |
| RTRS-16T | 16.000 | 8 | 560 x 420 x 110 | 200 x 200 x 110 | Ø 160 | 1100 | 76 | 4250116 |
| RTRS-24T | 24.000 | 12 | 750 x 450 x 110 | 256 x 200 x 110 | Ø 180 | 1100 | 106 | 4250124 |
| RTRS-36T | 36.000 | 18 | 780 x 550 x 110 | 300 x 550 x 110 | Ø 200 | 1500 | 148 | 4250136 |

TS roller skate for heavy machinery



REMA roller skate sets consist of 4 rollers, 2 bogies, 2 raising blocks, 2 steering rods and 2 connecting rods. Delivered in metal storage/transport case with the appropriate pull handle.

Applications

- Short, variable handling distances.
- For commissioning work and handling heavy loads.
- Due to the steering rods, large machines can be handled with ease.
- The handling speed may not exceed 5 m/min.
- Minimum turning cycle is 3 meter.

Norm:

- EN12100

| Type | WLL (kg) | Platform L x W x H (mm) | Turntable (mm) | Roller diameter (mm) | Weight (kg) | ProductId |
|-------|----------|-------------------------|----------------|----------------------|-------------|-----------|
| TS-20 | 20000 | 120 x 120 x 108 | 130 | 18 | 50 | 4211003 |
| TS-30 | 30000 | 120 x 120 x 117 | 130 | 24 | 58 | 4211005 |
| TS-60 | 60000 | 130 x 130 x 140 | 150 | 30 | 92 | 4211007 |

TRH roller type handspikes



Handspikes made of steel pipe are designed for a problem-free lifting of loads.

Norm:

- EN12100

| Type | WLL (kg) | Lever length (mm) | Lifting height (mm) | Roller diameter (mm) | Weight (kg) | ProductId |
|--------|----------|-------------------|---------------------|----------------------|-------------|-----------|
| TRH-15 | 1500 | 2000 | 130 | 70 x 55 | 13 | 4250040 |