


MD Power Puller

NOT FOR LIFTING




Lightweight POWER PULLER. With many applications when it comes to pulling, lashing and tensioning.

Properties


- Safety factor 4.
- Hooks equipped with safety latches.
- Anti-slip safety handle.
- Safe workload only with horizontal use.

Option

- 0310012 Wire pulling chain.
- 0310014 Barbed wire puller.



0310012



0310014

Type	WLL (kg)	Tension range (m)	Cable diameter (mm)	Weight (kg)	ProductId
MD-144 S	450	3.66	4.76	3.6	0310001
MD-144 SB	750	1.83	4.76	4.1	0310003

MDWS Band Puller

NOT FOR LIFTING



The flexible belt prevents damage to the material and controls the load.

Properties

- Safety factor 4.
- Hooks equipped with safety latches.
- Anti-slip safety handle.
- Non-conducting properties.
- Safe workload only with horizontal use.

Type	WLL (kg)	Tension range (m)	Webbing width (mm)	Webbing length (m)	Weight (kg)	ProductId
MDWS-1	225	3.5	25	3.66	3.3	0310005
MDWS-2	450	1.73	25	3.66	3.8	0310007
MDWS-25	225	3.05	25	7.62	3.5	0310009

MDA Rope puller

NOT FOR LIFTING



Lightweight and extremely robust POWER PULLER. Ideally suited for assembly work. With many application possibilities when it comes to pulling, lashing and tensioning.

Properties

- Safety factor 4.
- Hooks equipped with safety latches.
- Anti-slip safety handle.
- Non-conducting properties.
- Safe workload only with horizontal use.

Option

- Rope.

Type	WLL (kg)	Cable diameter (mm)	Weight (kg)	ProductId
MDA-0	350	12.7	3.2	0310011

IMPORTANT!

Before use, check steel wire rope, belt or rope for damages.
Before use, check that the hooks are not bent out and the safety latches are still attached.
Never extend the handle with a pipe for more power.
NOT FOR LIFTING.