

## REMA Select 200 Hand chain hoist



250 kg

The REMA Select 200 OD is equipped with an overload protection from 500 kg. It is a robust manual chain hoist for heavy and intensive use where safety, ergonomics and a low operating effort are paramount.

### Properties

- The new innovative overload protection ensures an improved safer operation of the hoist.
- Overload device system makes it possible to lower the load in a controlled way.
- Equipped with a double pawl system.
- Brake is provided with asbestos free friction discs.
- Top and bottom hooks are equipped with a robust latches.
- Load hooks gradually bend and do not break off suddenly.
- Galvanized load chain Grade 8.
- Galvanized hand chain.
- \* = without overload device.

**Overload Device provides more safety**  
\*Except 250 kg

### Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operating height.
- Overload protection from 500 kg up to 10.000 kg.

### Norm:


- EN12100-1/2, EN13157, EN818-7

### Option


- Available in any other hoisting and operational heights.
- Chain bag available up to 10 meter lifting height from 500 kg till 2000 kg.
- Short height in combination with REMA 211/212 trolley. (500/1000/2000 kg).




0.25t - 2.0t




3.0t - 5.0t



7.5t



10t



\* = without overload protection.

Type	WLL (kg)	Hand force max. (kg)	Load chain (mm)	Number of falls	Operating chain (mm)	Construction height (mm)	Weight (kg)	ProductId
S200-250KG*	250	23.5	4,0 x 12,0	1	5,0 x 23,7	260	6,0	0120000
S200OD-500KG	500	24,9	5,0 x 15,0	1	5,0 x 23,7	280	9,0	0120001
S200OD-1000KG	1.000	28,4	6,3 x 19,0	1	5,0 x 23,7	330	12,0	0120003
S200OD-1500KG	1.500	30,8	7,1 x 21,0	1	5,0 x 23,7	360	16,0	0120005
S200OD-2000KG	2.000	34,3	8,0 x 24,0	1	5,0 x 23,7	385	20,0	0120007
S200OD-3000KG	3.000	34,3	7,1 x 21,0	2	5,0 x 23,7	510	24,0	0120009
S200OD-5000KG	5.000	37,2	9,0 x 27,0	2	5,0 x 23,7	615	37,0	0120011
S200OD-7500KG	7.500	36,8	9,0 x 27,0	3	5,0 x 23,7	690	62,0	0120013
S200OD-10000KG	10.000	40,0	9,0 x 27,0	4	5,0 x 23,7	820	104,6	0120015

Type	A (mm)	B (mm)	C (mm)	D (mm)	H (mm)
S200-250KG*	108	106	20	30	260
S200OD-500KG	130	128	22	34	280
S200OD-1000KG	150	142	26	39	330
S200OD-1500KG	170	158	29	42	360
S200OD-2000KG	185	175	35	49	385
S200OD-3000KG	220	158	37	50	510
S200OD-5000KG	255	183	43	60	615
S200OD-7500KG	430	189	47	67	690
S200OD-10000KG	360	183	47	65	820