



C-rail



The standard length of C-rails for each profile sizes is appr. 6 m Orders shorter than 18 m are delivered in 3 m lengths for an easier transport.


Type	B (mm)	D (mm)	E (mm)	H (mm)	S (mm)	Capacity per meter (kg)	Weight (kg/pcs/m)	ProductId
PR100	8	30	15,8	28	1,75	80	1.3	4001001
PR300	11	40	19,8	35	2,75	100	2.5	4001003
PR400	15	48.5	24,8	43.5	3,20	200	3.8	4001005

Rail extensions




Type	B (mm)	H (mm)	L (mm)	S (mm)	Weight (kg/pcs/m)	ProductId
1103	38	36	85	3	0.3	4003001
1303	50	45	120	4	0.6	4003003
1403	60	54	150	4,5	1.0	4003005

Lateral fastener



Type	B (mm)	D (mm)	H (mm)	L (mm)	N (mm)	S (mm)	Weight (kg/pcs/m)	ProductId
101	38	8	60	40	10	3	0.15	4005001
301	50	11	76	55	13	4	0.35	4005003
401	60	13	94	68	16,5	4,5	0.5	4005005

Top fastener



Type	B (mm)	D (mm)	H (mm)	L (mm)	N (mm)	S (mm)	Weight (kg/pcs/m)	ProductId
102	90	8	39	40	63 ± 3.5	3	0.2	4007001
302	115	11	50	55	80 ± 4.0	4	0.35	4007003
402	130	13	59	60	94 ± 4.0	4,5	0.5	4007005