PT pallet truck



The new REMA PT pallet trucks fitted with pump (model 25) are very manoeuvrable and user-friendly. The tandem fork rollers are advantageous when using these pallet truck on a less smooth floor. Single truck roller designs are frequently used in the transport sector (rubber steer wheels and polyurethane rollers).

Properties

- Quick-Lift pump (model 25) for a quick lifting of pallets.
- The pump unit has an overload protection function.
- A chromate-coated and polished piston rod provides a long life for the hydraulic cylinder.

Operation:

- All pump functions can be operated precisely by means of the three-position control lever.
- Variable lowering speed even under load.
- The tow bar will automatically return to vertical position.

Fork:

- The robust plate steel fork profiles have flattened ends and they are fitted with in- and outrunning rollers to move pallets easier.

Technical specifications:

- Highest fork position: 200 mm.
- Steering wheel: 200 mm.
- Fork rolls: 82 mm.

Option

- Foot parking brake (3410000).

Norm:

- EN12100-1/2, EN 3691-5





Foot parking brake (3410000)



| Туре | WLL (kg) | Model | Dimensions (mm) | min height (mm) | width of fork (mm) | Material steering wheels | Model fork roller | Material fork rollers | Weight (kg) | ProductId |
|-------------|-------------|-------------|--------------------|--------------------|-----------------------|--------------------------|----------------------|-----------------------|----------------|-----------|
| PTS-25TPP | 2500 | Standard | 1150 x 540 | 85 | 160 | Polyurethane | Tandem | Polyurethane | 75 | 3410001 |
| PTK-25SPR-E | 2500 | Short | 1000 x 540 | 85 | 160 | Rubber | Single | Polyurethane | 86 | 3410005 |
| PTC-25SPR | 2500 | Extra short | 800 x 540 | 85 | 160 | Rubber | Single | Polyurethane | 75 | 3410017 |
| PTK-25TPR | 2500 | Short | 1000 x 540 | 85 | 160 | Rubber | Tandem | Polyurethane | 75 | 3410015 |
| PTS-25TPR | 2500 | Standard | 1150 x 540 | 85 | 160 | Rubber | Tandem | Polyurethane | 75 | 3410013 |
| PTSKB-25TPP | 2500 | Short/wide | 1000 x 680 | 85 | 160 | Polyurethane | Tandem | Polyurethane | 75 | 3410014 |
| PTS-25TNN | 2500 | Standard | 1150 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 75 | 3410011 |
| PTB-25TNN | 2500 | Standard | 1150 x 685 | 85 | 160 | Nylon | Tandem | Nylon | 80 | 3410012 |
| PTL-18TNN | 1800 | Long | 1500 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 80 | 3410021 |
| PTM-12TNN | 1200 | Medium long | 1800 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 80 | 3410025 |
| PTX-10TNN | 1000 | Extra long | 2000 x 540 | 85 | 160 | Nylon | Tandem | Nylon | 85 | 3410023 |

